

KIT/DH-PFM364L-D1/DH-IPC-HFW4230MP-4G-AS-I2/DH-PFB121W

Integrated Solar Monitoring System(without Lithium Battery)



System Overview

Integrated solar monitoring system (without lithium battery), all in one design, using 4G to transfer monitoring data and solar to power, which is easy/quick to install and can save wiring to the greatest extent, includes three parts: 4G network camera, integrated solar power system and camera's mounting bracket, which is more convenient for sale, order and transportation.

The integrated solar power system, integrating solar panels, maximum power point tracking (MPPT) charging controller and mounting brackets, provides stable power supply for the front-end data acquisition system—4G network camera through high conversion charging device. It is compact, portable, easy to install, disassemble and maintain compared with conventional system.

The 4G supported IR bullet camera delivers 2MP resolution with a 3.6 mm or 6 mm fixed lens. The camera can be connected to mobile internet as long as you have a SIM card, provides an excellent choice for a variety of small to mid-size applications such as off-grid system, farms, forest, border. Wall mount bracket of camera, support multi-angle flexible adjustment.

Functions

Integrated Aluminum Die Casting Casing

Compact structure integrated with solar panel, lithium battery pack and charging controller to improve the appearance, installation, and maintenance of the System.

Monocrystalline Solar Panel

Adopts monocrystalline solar panel to greatly improve optical absorbance efficiency and power generation performance with dusky light.

Remote Monitoring with APP

With Dahua cameras, it supports real-time remote monitoring of the system operation status and alarm prompts of battery with APP.

Solar Power System

- Integrated die casting casing
- Monocrystalline solar panel
- Aluminum alloy frame
- Remote monitoring with APP
- Maximum Power Point Tracking (MPPT) charging controller
- RS-485 communication function
- Electronic protection

4G Network Camera

- 1/2.9" 2Megapixel progressive CMOS
- H.265 & H.264 dual-stream encoding
- 25/30 fps@2M (1920×1080)
- Day/Night (ICR), 3DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS (DSS/PSS) & DMSS
- Micro SD card slot, up to 256 GB
- 3.6 mm, 6 mm fixed lens
- Max. IR LEDs length 40 m
- 4G supported
- IP67



Maximum Power Point Tracking Charging Controller (MPPT)

MPPT controller helps significantly improve the energy utilization efficiency of the System, and raise the charging efficiency by 10%–30% compared with conventional PWM controller.

RS-485 Port

RS-485 port and standard Modbus protocol, meeting communication requirements in various scenarios.

Electronic Protection

Comprehensive electronic protection: Current limiting, short circuit, and reverse current protection of solar panel; reverse connection, overvoltage, over-discharge, and over-temperature protection of lithium battery; overload and short circuit protection of load.

4G

The camera can be connected to Mobile Internet as long as you have a SIM card, then you can place it anywhere and no need to worry about the wiring hassles.

Intelligent Video Analysis (IVS)

Dahua camera is equipped with a built-in intelligent analytic algorithm based on video, which can realize intelligent functions like Tripwire and Intrusion, to quickly and accurately respond to monitoring events in specific area, It can enhance monitoring efficiency. In addition, the

camera supports intelligent tamper detection, which is to generate warning message via detecting dramatic scene change and to guarantee effective video surveillance.

Smart IR Technology

With IR illumination, detailed images can be captured in low light or total darkness. The camera's Smart IR technology adjusts the intensity of camera's infrared LEDs to compensate the distance of an object. Smart IR technology prevents IR LEDs from whitening out images as they come closer to the camera. The camera's integrated infrared illumination provides high performance in extreme low-light environments up to 80 m (262.5 ft).

Protection (IP67, Wide Voltage)

The camera allows for ±25% input voltage tolerance, suitable for the most unstable conditions for outdoor applications. Its 2KV lightning rating provides effective protection for both the camera and its structure against lightning. Subjected and certified to rigorous dust and immersion tests (IP67), the camera is the choice for installation in even the most unforgiving environments.

Environmental

Dahua cameras operate in extreme temperature environments, rated for use in temperatures from -30° C to +60° C (-22° F to +140° F) with 95% humidity.

Smart Codec (H.265+ & H.264+)

Smart Codec is the optimized implementation of standard video compression (H.265 & H.264) that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality video without straining the network. Smart Codec technology reduces bit rate and storage requirements by up to 70% when compared to the standard video compression.

Technical Specification	
Integrated Solar Power System (without Lithium Battery)	
Model	DH-PFM364L-D1
Solar Panel	
Type	Monocrystalline silicon
Max. Power	60W
Solar Cell Efficiency	21%
Max. Mechanical Load	5400Pa
Protection	
Over-discharge Protection Voltage	11.1V DC
Low Temperature Charging	≤-10°C (14°F)
Low Temperature Discharging	≤-20°C (-4°F)
Grade	IP66
Others	Over temperature, overvoltage of the battery, overload, and short circuit

Port	
Power Output	Φ5.5 mm × Φ2.1 mm × 12 mm(Φ0.22" × Φ0.08" × 0.47")
RS-485	1

General	
Main Body Material	Die casting aluminum
Installation	Pole mount, installed on 76 mm to 96 mm (Φ3.0"–Φ3.78") poles
Adjustable Angle	Horizontal: 0°–360° Vertical: -75°–80°
Product Dimensions	1149.5 mm × 367.6 mm × 430.2 mm (45.26" × 14.47" × 16.94")
Packaging Dimensions	1353 mm × 548 mm × 364 mm (53.27" × 21.57" × 14.33")
Packaging Method	1 pc in each carton
Net Weight	16 kg (35.27 lb)
Gross Weight	22.5 kg (49.60 lb)

Environment	
Operating Altitude	<3000 m (9842.5 ft)
Applicable Area	Areas with daily solar radiation>4.5 h
Operating Temperature	-20°C to 60°C (-4°F to 140°F)
Operating Humidity	<95% (RH)
Storage Temperature	0°C to 40°C (32°F to 104°F)
Storage Humidity	<95% (RH)

Certifications	
Certifications	CE: EN61000-6-2, EN61000-6-4 FCC: FCC Part 15 Subpart B

2MP 4G IR Bullet Network Camera	
Model	DH-IPC-HFW4230M-4G-AS-I2
Camera	
Image Sensor	1/2.9" 2Megapixel progressive scan CMOS
Effective Pixels	1920(H) × 1080(V)
RAM/ROM	256 MB/32 MB
Scanning System	Progressive
Minimum Illumination	0.04 Lux/F2.0 (Color,1/3 s,30IRE) 0.22 Lux/F2.0 (Color,1/30 s,30IRE) 0 Lux/F2.0 (IR on)
S/N Ratio	More than 56 dB
IR Distance	Distance up tp 40 m (131.2 ft)
IR On/Off Control	Auto/ Manual
IR LEDs	2
Lens	
Lens Type	Fixed
Mount Type	M12
Focal Length	3.6 mm (6 mm optional)

Max. Aperture	F2.0				
Angle of View	H: 82.5° (51.5°), V: 44° (29.5°)				
Optical Zoom	N/A				
Focus Control	Fixed				
Close Focus Distance	0.9 m (2 m) 29.5 ft (6.56 ft)				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	3.6 mm	53 m (174 ft)	21 m (69 ft)	10 m (33 ft)	5 m (17 ft)
	6 mm	80 m (262 ft)	32 m (105 ft)	16 m (52 ft)	8 m (26 ft)

Pan/Tilt/Rotation

Pan/Tilt/Rotation Range	N/A
-------------------------	-----

Intelligence

Event Trigger	Motion detection, Video tampering, Scene changing, Network disconnection, IP address conflict, Illegal Access, Storage anomaly
IVS	Tripwire, Intrusion

Video

Compression	H.265/H.264H/MJPEG (Sub Stream)
Smart Codec	Support H.265/H.264
Streaming Capability	2 Streams
Resolution	1080P (1920 × 1080)/1.3M (1280 × 960)/720P (1280 × 720)/D1 (704 × 576)/720P (1280 × 720)/D1 (704 × 576)/VGA (640 × 480)/CIF (352 × 288)
Frame Rate	Main Stream: 1080P@25 fps Sub Stream: D1@25 fps
Bit Rate Control	CBR/VBR
Bit Rate	H.264: 32–10240 Kbps; H.265: 12–6400 Kbps
Day/Night	Auto ICR
BLC Mode	BLC / HLC / DWDR
White Balance	Auto/Natural/Street Lamp/Outdoor/Manual
Gain Control	Auto
Noise Reduction	3D DNR
Motion Detection	Off/On (4 Zone, Rectangle)
Region of Interest	Off/On (4 Zone)
Electronic Image Stabilization(EIS)	N/A
Smart IR	Yes
Defog	N/A
Digital Zoom	N/A
Flip	0°/90°/180°/270°
Mirror	Off/On
Privacy Masking	Off/On (4 Areas, Rectangle)

Audio

Compression	G.711a/G.711Mu/AAC/G.726
-------------	--------------------------

Network

Ethernet	RJ-45 (10/100Base-T)
Mobile Communication	4G
Operating band	Model 1: TDD-LTE: Band38/39/40/41 FDD-LTE: Band1/3/5/8 WCDMA: Band1/8 TD-SCDMA: Band34/39 EVDO/CDMA1X: BCO GSM: Band3/8 Model 2: FDD-LTE: Band1/2/3/4/5/7/8/20 UMTS: Band1/2/5/8 GSM: 850/900/1800/1900
Protocol	HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPV4/IPv6; QoS; UPnP; NTP; Bonjour; IEEE 802.1X; Multicast; ICMP; IGMP; TLS
Interoperability	ONVIF Profile S&G, API
Streaming Method	Unicast/Multicast
Max. User Access	10 Users/20 Users
Edge Storage	NAS Local PC for instant recording Mirco SD card 256 GB
Web Viewer	IE, Chrome, Firefox, Safari
Management Software	Smart PSS, DSS, DMSS
Smart Phone	iOS, Android

Certifications

Certifications	CE-LVD: EN60950-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B
Smart Phone	iOS, Android

Interface

Audio Interface	1/1 channel In/Out
Alarm	2 channels In: 500mA 5VDC 2 channels Out: 300mA 12VDC

Electrical

Power Supply	DC12V±30%
Power Consumption	3.6W, 9.5W (IR on);6W (4G on, IR off)

Environmental

Operating Conditions	-30°C to +60°C (-22°F to +140°F)/Less than 95% RH
Storage Conditions	-30°C to +60°C (-22°F to +140°F)/Less than 95% RH
Ingress Protection	IP67
Vandal Resistance	N/A

Construction

Casing	Metal+Plastic
Dimensions	194.4 mm × 96.6 mm × 89.5 mm (7.65" × 3.8" × 3.52")
Net Weight	0.7 kg (1.54 lb)
Gross Weight	0.8 kg (1.76 lb)

Wall Mount Bracket

Model	DH-PFB121W
-------	------------

General

Material	Aluminum
Dimension (W×H×D)	58 mm × 88 mm × 190.5 mm (2.28" × 3.46" × 7.50")
Weight	0.24 kg (0.53 lb)
Load Bearing	1 kg (2.2 lb)
Color	White
Operating Temperature	-40°C to +60°C (-40°F to +140°F)
Humidity	<90% RH
Applicable Model	Please check "Accessory Selector" on DAHUA website

Application



Ordering Information

Type	Part Number	Description
Power Series	KIT/DH-PFM364L-D1/DH-IPC-HFW4230MP-4G-AS-I2/DH-PFB121W	KIT: 60W integrated solar power system((without Lithium Battery))/4G bullet camera/ PFB121W
Optional	PFM372-L45-4S14P	Integrated solar lithium battery

Dimensions (mm[inch])

