PP2711 / 2022 / ISSUE 2 **DATASHEET SOTERIA UL SWITCH MONITOR MODULE**





PRODUCT OVERVIEW

Product	Switch Monitor Module
Part No.	SA4705-700AP0
Digital Communication	XP95 and Discovery

PRODUCT INFORMATION

The Switch Monitor Module is a loop-powered device incorporating a monitored input circuit for connection to remote switches, for indoor use only.

- Built-in isolator
- Visible LEDs
- Loop Powered
- Ground fault detection
- Selectable priority to monitor equipment where a fast response is required
- Interrupt facility
- Improved design for ease of wiring

TECHNICAL DATA

I ED Color

All data is supplied subject to change without notice Specifications are typical at 24 V, 73°F and 50% RH unless otherwise stated.

	General
Product Operating Temperature	32°F to 120°F
Humidity	10% to 93% RH (no condensation or icing)
Standards and Approvals	UL, ULC, FM, CSFM
Dimensions	4.9" W x 4.9" H x 1.175" D
Materials	Housing: UL94 V-0 polycarbonate
Wire Size	12 - 24 AWG

LED Status

Description VP05/Discovery

LED Color	Description	Compatibility
Green	Polling	X
Yellow (solid)	Isolation	X
Red	Alarm	X
Single Line Cirvuit (SLC) - Supervised Power Limited		
Supply Voltage	17 V to 28 V DC	
Modulation Voltage	5 V - 9 V peak to	peak
Supervisory Current	500 μΑ	
Switch-on Surge Current	900 μΑ	
Alarm/Operated Current, LED ON	1.6 mA per LED	
Maximum Loop Current	1 A	
Initiating Device Circuit (IDC)		

Wiring Styles	Supervised power limited Class A and Class B
Voltage	3.3 V DC
Line Impedance	100 Ω Max
End-of-Line Resistors*	47 kΩ

*Note: A UL listed end-of-line resistor is available at Apollo - Part No. 44251-146

APPROVALS











25 Corporate Drive, Auburn Hills, MI 48326 Tel: (248)332-3900. Fax: (248)332-8807

Email: sales.usa@apollo-fire.com www.apollo-fire.com





